

18/PRTS

10/525407
DT01 Rec'd PCT/PTC 23 FEB 2005

SPECIFICATION

OPTICAL WAVELENGTH MULTIPLEX ACCESS SYSTEM AND OPTICAL NETWORK UNIT

5

TECHNICAL FIELD

The present invention relates to an optical wavelength-division multiple access system that facilitates installation of additional optical network units in a system that bidirectionally transmits optical signals between a center apparatus (OLT: Optical Line Terminal) and a plurality of optical network units (ONUs: Optical Network Units), as well
10
15 corresponding optical network units.

BACKGROUND ART

FIG. 1A shows an example of the configuration of a conventional optical wavelength-division multiplex(ing) (WDM) access system (Japanese Patent Application Laid-open No. 2000-196536). In FIG. 1A, a center apparatus (OLT) 50 and a wavelength multi/demultiplex(ing) apparatus 60 are connected
20
25 together in a multiplex section via multiplex section optical fibers 1 and 2. The wavelength multi/demultiplex(ing) apparatus 60 and a plurality of

optical network units (ONUs) 70-1 to 70-n are connected together in an access section via access section optical fibers 3 and 4. In this case, one wavelength band D is assigned to downlink signals from the OLT to the ONUs. One wavelength band U (\neq D) is assigned to uplink signals from the ONUs to the OLT. In the example shown below, wavelengths λ_{d1} to λ_{dn} in the wavelength band D and wavelengths λ_{u1} to λ_{un} in the wavelength band U are assigned to the respective ONUs.

A transmission section (S) 51 of the OLT 50 multiplexes the wavelengths of a downlink optical signal within the wavelength band D (λ_{d1} to λ_{dn}) and of an optical carrier for an uplink signal within the wavelength band U (λ_{u1} to λ_{un}). The transmission section (S) 51 then transmits the resulting signals to the wavelength multi/demultiplex(ing) apparatus 60. The wavelength multi/demultiplex(ing) apparatus 60 divides the downlink optical signal within the wavelength band D and the optical carrier for the uplink signal within the wavelength band U into the respective wavelengths. The wavelength multi/demultiplex(ing) apparatus 60 transmits, via the access section optical fiber 3, the pairs of the downlink optical signals of the wavelengths λ_{d1} to λ_{dn} and uplink optical carrier of the wavelengths λ_{u1} to λ_{un} obtained by the division and corresponding ONUs

70-1 to 70-n.

The ONU 70-1 uses a WDM coupler 71 to demultiplex the downlink optical signal of the wavelength λ_{d1} from the optical carrier for the uplink signal of the wavelength λ_{u1} , the signal and carrier having been transmitted. The ONU 70-1 further uses an optical receiver (R) 72 to receive the downlink optical signal of the wavelength λ_{d1} . The ONU 70-1 also uses an optical modulator (M) 73 to obtain an uplink optical signal from the optical carrier for the uplink signal and then transmits the signal to the wavelength multi/demultiplex(ing) apparatus 60 via the access section optical fiber 4. This also applies to the other ONUs. The wavelength multi/demultiplex(ing) apparatus 60 multiplexes the wavelengths of the uplink optical signals of the wavelengths λ_{u1} to λ_{un} transmitted by the ONUs. The uplink optical signals wavelength-multiplexed are transmitted to the OLT 50 via the multiplex section optical fiber 2. A reception section (R) 52 then receives the signals.

In this case, as shown in FIG. 1B, the wavelength band D (wavelength λ_{d1} to λ_{dn}) for the downlink optical signals and the wavelength band U (wavelength λ_{u1} to λ_{un}) for the uplink optical signals (the optical carrier for the uplink signal) are arranged so as not to overlap on a wavelength axis. An arrayed waveguide grating (AWG) 61 used as the wavelength

multi/demultiplex(ing) apparatus 60 has a function for demultiplexing and sending a downlink signal

wavelength (for example, λ_{d1}) and uplink signal

wavelength (for example, λ_{u1}) within an FSR (Free

5 Spectral Range) to the same port. A pair of a downlink optical signal having a wavelength within the

wavelength band D and an uplink optical signal having

a wavelength within the wavelength band U are input to

each ONU. Thus, as shown in FIG. 1C, by using WDM

10 couplers 71 conforming to the same specifications and

which separate the wavelength bands D and N from each

other, it is possible to separate the downlink optical

signal from the uplink optical signal to prevent their mutual interferences.

15 A method has been proposed with which when the

transmission section 51 of the OLT 50 transmits

optical carriers for uplink signals of the wavelengths

λ_{u1} to λ_{un} , broadband light containing the wavelengths

λ_{u1} to λ_{un} is used and with which the AWG 61 of the

20 wavelength multi/demultiplex(ing) apparatus 60

spectrum-slices the light to obtain optical carriers

for uplink signals of the wavelengths λ_{u1} to λ_{un} , which

are then supplied to the ONUs (Japanese Patent

Application Laid-open No. 2001-177505).

25 Such improvements are intended to allow the ONUs

70-1 to 70-n to be composed of common devices (a

reduction in the number of types of devices).

Specifically, the OLT 50 supplies optical carriers for uplink signals of the respective wavelengths to the corresponding ONUs. Thus, the ONUs need not comprise the respective light sources for the assigned

5 wavelengths. The ONUs can utilize optical modulators 73 conforming to the same specifications, for the wavelength band U. Moreover, one downlink signal within the wavelength band D and one uplink signal within the wavelength band U are input to each ONU.

10 The ONUs can use the WDM couplers 71 conforming to the same specifications and which separate the wavelength bands D and U from each other, in order to separate the downlink optical signal from the optical carrier for the uplink signal.

15 Further, in a configuration in which the OLT 50 is located opposite the plurality of ONUs 70-1 to 70-n via the AWG 61 or multiport wavelength filters as shown in FIG. 2A, the use of a wavelength variable light source as an optical transmitter (S) 75 makes it
20 possible to arrange optical transmitters conforming to the same specifications, in the ONUs. In this case, the ONUs 70-1 to 70-n transmit uplink optical signals of the different wavelengths λ_{u1} to λ_{un} ; FIG. 2B shows the wavelength characteristics of the ONUs.

25 Moreover, similarly, in connection with a configuration shown in FIG. 2A, a proposal described below has been proposed (Akimoto, K, et al.,

"Spectrum-sliced, 25-GHz spaced, 155Mbps x 32 channel WDM access", The 4th Pacific Rim Conference on Lasers and Electro-Optics, 2001 (CLEO/Pacific Rim 2001), Vol. 2, pp.II-556-557). The optical transmitter 75 of each
5 ONU modulates broadband light having a wide spectrum width in the wavelength band U; FIG. 2C shows the wavelength characteristics of the optical transmitter 75. Each ONU modulates the broadband light to obtain an uplink optical signal and then transmits the signal.
10 The wavelength multi/demultiplex(ing) apparatus 60 spectrum-slices the uplink optical signal to multiplex their wavelengths and then transmits the resultant signals to the OLT 50. This configuration is substantially equivalent to that in which the ONUs
15 transmit uplink optical signals of different wavelengths. However, this configuration is characterized in that optical transmitters conforming to the same specifications can be arranged in the ONUs.

It is possible to use an electric signal to
20 directly modulate a superluminescent diode or a semiconductor optical amplifier (SOA) in order to obtain modulated light of a large optical spectral width. Alternatively, it is possible to use an external modulator to modulate output light (broadband
25 non-modulated light) from a semiconductor optical amplifier or an erbium-doped fiber amplifier (EDFA).

If ONUs accommodated in the OLT are added to a

conventional optical wavelength-division
multiplex(ing) system, different wavelength bands are
set for the wavelengths assigned to the standard ONUs
and for the wavelengths assigned to the additional
5 ONUs. In general, a configuration such as the one
shown in FIG. 3 is possible. Basically, in this
configuration, a standard and additional versions of
each component are arranged in parallel; the
components include the transmission section 51 and
10 reception section 52 of the OLT 50, the AWG 61 of the
wavelength multi/demultiplex(ing) apparatus 60, and
the ONUs 70-1 to 70-n, all of which are shown in FIG.
1.

In this case, the wavelengths λ_{d1} to λ_{dn} of a
15 wavelength band Da for downlink signals and the
wavelengths λ_{u1} to λ_{un} of a wavelength band Ua for
uplink signals are assigned to the standard ONUs 70-1
to 70-n. Further, the wavelengths λ_{dn+1} to λ_{dn+m} of a
wavelength band Db for downlink signals and
20 wavelengths λ_{un+1} to λ_{un+m} of a wavelength band Ub for
uplink signals are assigned to additional ONUs 70-n+1
to 70-n.

The OLT 50 comprises a standard transmission
section (Sa) 51a that multiplexes the wavelengths of
25 and transmits downlink optical signals in the
wavelength band Da (λ_{d1} to λ_{dn}) and optical carriers
for uplink signals in the wavelength band Ua (λ_{u1} to

λ_{un}). The OLT 50 also comprises an additional transmission section (Sb) 51b that multiplexes the wavelengths of and transmits downlink optical signals in the wavelength band Db (λ_{dn+1} to λ_{dn+m}) and optical carriers for uplink signals in the wavelength band Ub (λ_{un+1} to λ_{un+m}). Moreover, the OLT 50 comprises a standard reception section (Ra) 52a that receives optical signals in the wavelength band Ua (λ_{u1} to λ_{un}) and an additional reception section (Rb) 52b that receives optical signals in the wavelength band Ub (λ_{un+1} to λ_{un+m}).

A WDM coupler 53d multiplexes the wavelengths of standard and additional downlink optical signals and optical carriers for uplink signals transmitted by the standard transmission section 51a and the additional transmission section 51b. The WDM coupler 53d then transmits the resultant signals to the wavelength multi/demultiplex(ing) apparatus 60 via the multiple section optical fiber 1. The wavelength multi/demultiplex(ing) apparatus 60 uses a WDM coupler 62d to separate the standard wavelength bands Da and Ua from the additional wavelength bands Db and Ub. The wavelength multi/demultiplex(ing) apparatus 60 uses AWGs 61a and 61b to divide the wavelength bands separated, into downlink optical signals and optical carriers for uplink signals of the respective wavelengths. Pairs of downlink optical signals of the

wavelengths λ_{d1} to λ_{dn} and optical carriers for uplink signals of the wavelengths λ_{u1} to λ_{un} which have been divided by the AWG 61a are transmitted to the corresponding ONUs 70-1 to 70-n via the access section optical fiber 3. Pairs of downlink optical signals of the wavelengths λ_{dn+1} to λ_{dn+m} and optical carriers for uplink signals of the wavelengths λ_{un+1} to λ_{un+m} which have been divided by the AWG 61b are transmitted to the corresponding ONUs 70-n+1 to 70-n+m via the access section optical fiber 3.

WDM couplers 71a of the standard ONUs 70-1 to 70-n are equally characterized by demultiplexing the wavelength bands D_a and U_a . Optical modulators 73a of the standard ONUs 70-1 to 70-n are equally characterized by modulating optical carriers of the wavelength band U_a . On the other hand, WDM couplers 71b of the standard ONUs 70-n+1 to 70-n+m are equally characterized by demultiplexing the wavelength bands D_b and U_b . Optical modulators 73b of the standard ONUs 70-n+1 to 70-n+m are equally characterized by modulating optical carriers of the wavelength band U_b . Uplink optical signals transmitted by each pair of ONUs are transmitted to the AWGs 61a and 61b of the wavelength multi/demultiplex(ing) apparatus 60 via the access section optical fiber 4. Then, a WDM coupler 62u demultiplexes the standard and additional uplink optical signals wavelength-multiplexed. The WDM

coupler 62u then transmits the resultant signals to the OLT 50 via the uplink multiple section optical fiber 2. The OLT 50 uses a WDM coupler 53u to separate the standard wavelength band Ua from the additional
5 wavelength band Ub. The standard and additional reception sections 52a and 52b receive the wavelength bands separated.

A wavelength-division multiplex(ing) access system shown in FIG. 3 is obtained simply by expanding the
10 conventional wavelength-division multiplex(ing) access system shown in FIG. 1A. As shown in FIG. 4A, the wavelengths λ_{d1} to λ_{dn} of the wavelength band Da are assigned to standard downlink signals. The wavelengths λ_{un+1} to λ_{un+m} of the wavelength band Ua are assigned
15 to standard uplink signals. The wavelengths λ_{dn+1} to λ_{dn+m} of the wavelength band Db are assigned to additional downlink signals. The wavelengths λ_{un+1} to λ_{un+m} of the wavelength band Ub are assigned to standard downlink signals. Further, the wavelength
20 bands Ua, Da, Ub, and Db are assigned to the wavelength axis on this order.

With this assignment, as shown in FIG. 4B, the transmission characteristics of the WDM couplers 53d and 53u of the OLT 50 and of the WDM couplers 62d and
25 62u of the wavelength multi/demultiplex(ing) apparatus 60 may be such that they can merge or separate the standard wavelength bands Ua and Da with or from the

additional wavelength bands U_b and D_b . Accordingly, all of these components may conform to the same specifications.

5 However, the WDM couplers 71a of the standard ONUs 70-1 to 70-n separate the wavelength bands U_a and D_a from each other. The WDM couplers 71b of the additional ONUs 70-n+1 to 70-n+m separate the wavelength bands U_b and D_b from each other. Accordingly, these components require different
10 transmission characteristics as shown in FIGS. 4C and 4D. Similarly, the operating bands of the standard and additional optical modulators 73a and 73b are different, the standard and additional optical modulators 73a and 73b operate in the wavelength bands
15 U_a and U_b , respectively, as shown in FIGS. 4E and 4F. In other words, for the standard and additional ONUs, the WDM couplers 71a and 71b must conform to different specifications, and the optical modulators 73a and 73b conform to different specifications.

20 Common devices can be used as the WDM couplers 71a and 71b if they have a transmission characteristic such that the wavelength bands D_a and U_b can be separated from the wavelength bands U_a and D_b , shown in FIG. 4G. However, different optical receivers and
25 different connection ports must be used for the standard and additional WDM couplers and the standard and additional optical modulators, respectively. Thus,

this configuration does not actually allow all the ONUs to be composed of common devices. Further, common devices can be used as both optical modulators 73a and 73b provided that they operate over a broad band spanning the wavelength bands U_a , D_a , and U_b . However, the operating band is now limited to about several 10s of nm. Accordingly, the number of wavelengths (ONUs) is not enough to allow the optical modulators 73a and 73b to be composed of only one type of component.

These light emission bands are also a limiting factor for a configuration in which an optical transceiver 75 that modulates a wavelength variable light source or a broadband light is placed in each ONU as shown in FIG. 2B or 2C.

It is an object of the present invention to provide a wavelength-division multiplex(ing) access system which allows standard and additional ONUs to conform to the same specifications and which can minimize an operating band for an optical modulator or a light emission band for an optical transmitter.

DISCLOSURE OF THE INVENTION

To accomplish the above object, the present invention provides a wavelength-division multiple access system having a center apparatus (OLT), n optical network units (ONU), and m ONUs arranged via a

wavelength multi/demultiplex apparatus, the OLT and the wavelength multi/demultiplex apparatus being connected together in a multiplex section via multiplex section optical fibers, the wavelength multi/demultiplex apparatus and the ONUs being connected together in an access section via access section optical fibers, downlink optical signals from the OLT to the ONUs and uplink optical signals from the ONUs to the OLT being transmitted through the multiplex section using wavelengths assigned to the respective ONUs while multiplexing the wavelengths, the wavelength multi/demultiplex apparatus carrying out wavelength multiplexing or demultiplexing for bidirectional transmissions, characterized in that a wavelength band Da (wavelengths λ_{d1} to λ_{dn}) for downlink optical signals corresponding to the n ONUs, a wavelength band Ua (wavelengths λ_{u1} to λ_{un}) for uplink optical signals corresponding to the n ONUs, a wavelength band Db (wavelengths λ_{dn+1} to λ_{dn+m}) for downlink optical signals corresponding to the m ONUs, and a wavelength band Ub (wavelengths λ_{un+1} to λ_{un+m}) for uplink optical signals corresponding to the m ONUs are set different from one another, the wavelength bands Ua and Ub are set adjacent to each other, and the wavelength bands Ua and Da or the wavelength bands Ub and Db are set adjacent to each other, and in that each of the ONUs comprises downlink optical signal

receiving means for receiving a downlink optical signal of one of the wavelengths λ_{d1} to λ_{dn+m} in the wavelength bands D_a and D_b which wavelength is assigned to the ONU, and uplink optical signal transmitting means for transmitting an uplink optical signal of one of the wavelengths λ_{u1} to λ_{un+m} in the wavelength bands U_a and U_b which wavelength is assigned to the ONU or an uplink optical signal within a broad band including the wavelength bands U_a and U_b .

Further, to accomplish the above object, the present invention provides an optical network unit (ONU) used in a wavelength-division multiple access system having a center apparatus (OLT), n ONUs, and m ONUs arranged via a wavelength multi/demultiplex apparatus, the OLT and the wavelength multi/demultiplex apparatus being connected together in a multiplex section via a multiplex section optical fiber, the wavelength multi/demultiplex apparatus and the ONUs being connected together in an access section via an access section optical fiber, downlink optical signals from the OLT to the ONUs and uplink optical signals from the ONUs to the OLT being transmitted through the multiplex section using wavelengths assigned to the respective ONUs while multiplexing the wavelengths, the wavelength multi/demultiplex apparatus carrying out wavelength multiplexing or demultiplexing for bidirectional transmissions,

characterized in that a wavelength band Da
(wavelengths λ_{d1} to λ_{dn}) for downlink optical signals
corresponding to the n ONUs, a wavelength band Ua
(wavelengths λ_{u1} to λ_{un}) for uplink optical signals
5 corresponding to the n ONUs, a wavelength band Db
(wavelengths λ_{dn+1} to λ_{dn+m}) for downlink optical
signals corresponding to the m ONUs, and a wavelength
band Ub (wavelengths λ_{un+1} to λ_{un+m}) for uplink optical
signals corresponding to the m ONUs are set different
10 from one another, the wavelength bands Ua and Ub are
set adjacent to each other, and the wavelength bands
Ua and Da or the wavelength bands Ub and Db are set
adjacent to each other, and in that each of the ONUs
comprises downlink optical signal receiving means for
15 receiving a downlink optical signal of one of the
wavelengths λ_{d1} to λ_{dn+m} in the wavelength bands Da and
Db which wavelength is assigned to the ONU, and uplink
optical signal transmitting means for transmitting an
uplink optical signal of one of the wavelengths λ_{u1} to
20 λ_{un+m} in the wavelength bands Ua and Ub which
wavelength is assigned to the ONU or an uplink optical
signal within a broad band including the wavelength
bands Ua and Ub.

Further, to accomplish the above object, the
25 present invention provides an optical network unit
(ONU) used in a wavelength-division multiple access
system having a center apparatus (OLT), n ONUs, and m

ONUs arranged via a wavelength multi/demultiplex apparatus, the OLT and the wavelength multi/demultiplex apparatus being connected together in a multiplex section via a multiplex section optical fiber, the wavelength multi/demultiplex apparatus and the ONUs being connected together in an access section via an access section optical fiber, downlink optical signals from the OLT to the ONUs and uplink optical signals from the ONUs to the OLT being transmitted through the multiplex section using wavelengths assigned to the respective ONUs while multiplexing the wavelengths, the wavelength multi/demultiplex apparatus carrying out wavelength multiplexing or demultiplexing for bidirectional transmissions, characterized in that a wavelength band D_a (wavelengths λ_{d1} to λ_{dn}) for downlink optical signals corresponding to the n ONUs, a wavelength band U_a (wavelengths λ_{u1} to λ_{un}) for uplink optical signals corresponding to the n ONUs, a wavelength band D_b (wavelengths λ_{dn+1} to λ_{dn+m}) for downlink optical signals corresponding to the m ONUs, and a wavelength band U_b (wavelengths λ_{un+1} to λ_{un+m}) for uplink optical signals corresponding to the m ONUs are set different from one another, the wavelength bands U_a and U_b are set adjacent to each other, and the wavelength bands U_a and D_a or the wavelength bands U_b and D_b are set adjacent to each other, in that a connection is made

to each ONU in the access section via two access
section optical fibers, in that the OLT is configured
to multiplex the wavelengths of and transmit optical
carriers for uplink signals in the wavelength bands Ua
5 and Ub (wavelengths λ_{u1} to λ_{un+m}) and downlink optical
signals in the wavelength bands Da and Db (wavelengths
 λ_{d1} to λ_{dn+m}) to the multiplex section optical fiber,
in that the wavelength multi/demultiplex apparatus is
configured to separate the optical carriers for uplink
10 signals and downlink optical signals of the
wavelengths corresponding to the ONUs from the optical
carriers for uplink signals and downlink optical
signals input via the multiplex section optical fiber
and to output the resultant signals to the ONUs via
15 one of the access section optical fibers, while
multiplexing the uplink optical signals input through
the other access section optical fiber and having the
wavelengths corresponding to the ONUs to output the
resultant signals to the multiplex section optical
20 fiber, and in that each of the ONUs comprises a
wavelength band demultiplexer which is characterized
by separating the wavelength bands Ua and Ub for
uplink optical signals from the wavelength bands Da
and Db for downlink optical signals and which
25 demultiplexes the optical carrier for the uplink
signal from the downlink optical signal, the optical
carrier for the uplink signal and the downlink optical

signal being input via one of the access section optical fibers and having the wavelengths corresponding to the ONU, downlink optical signal receiving means for receiving a downlink optical signal of one the wavelengths λ_{d1} to λ_{dn+m} in the wavelength bands D_a and D_b demultiplexed by the wavelength band demultiplexer which wavelength is assigned to the ONU, and uplink optical signal transmitting means for consisting of an optical modulator modulating an optical carrier for an uplink signal of one of the wavelengths λ_{u1} to λ_{un+m} in the wavelength bands U_a and U_b demultiplexed by the wavelength band demultiplexer which wavelength is assigned to the ONU, the optical modulator then transmitting the resultant signal to the other access section optical fiber.

Further, to accomplish the above object, the present invention provides an optical network unit (ONU) used in a wavelength-division multiple access system having a center apparatus (OLT), n ONUs, and m ONUs arranged via a wavelength multi/demultiplex apparatus, the OLT and the wavelength multi/demultiplex apparatus being connected together in a multiplex section via a multiplex section optical fiber, the wavelength multi/demultiplex apparatus and the ONUs being connected together in an access section via an access section optical fiber, downlink optical

signals from the OLT to the ONUs and uplink optical signals from the ONUs to the OLT being transmitted through the multiplex section using wavelengths assigned to the respective ONUs while multiplexing the

5 wavelengths, the wavelength multi/demultiplex apparatus carrying out wavelength multiplexing or demultiplexing for bidirectional transmissions, characterized in that a wavelength band Da (wavelengths λ_{d1} to λ_{dn}) for downlink optical signals

10 corresponding to the n ONUs, a wavelength band Ua (wavelengths λ_{u1} to λ_{un}) for uplink optical signals corresponding to the n ONUs, a wavelength band Db (wavelengths λ_{dn+1} to λ_{dn+m}) for downlink optical signals corresponding to the m ONUs, and a wavelength

15 band Ub (wavelengths λ_{un+1} to λ_{un+m}) for uplink optical signals corresponding to the m ONUs are set different from one another, the wavelength bands Ua and Ub are set adjacent to each other, and the wavelength bands Ua and Da or the wavelength bands Ub and Db are set

20 adjacent to each other, in that a connection is made to each ONU in the access section via one access section optical fiber, and in that each of the ONUs comprises a wavelength band demultiplexer which is characterized by separating the wavelength bands Ua

25 and Ub for uplink optical signals from the wavelength bands for downlink optical signals and which outputs a downlink optical signal input via the access section

optical fiber and having the wavelength corresponding to the ONU, to downlink optical signal receiving means, while outputting an uplink optical signal output by uplink optical signal transmitting means and having
5 the wavelength corresponding to the ONU, to the access section optical fiber, downlink optical signal receiving means for receiving a downlink optical signal of one of the wavelengths λ_{d1} to λ_{dn+m} in the wavelength bands D_a and D_b which wavelength is
10 assigned to the ONU, and uplink optical signal transmitting means for transmitting an uplink optical signal of one of the wavelengths λ_{u1} to λ_{un+m} in the wavelength bands U_a and U_b which wavelength is assigned to the ONU or an uplink optical signal within
15 a broad band including the wavelength bands U_a and U_b .

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A to 1C are diagrams showing an example of
20 the configuration of a conventional optical wavelength-division multiplex(ing) access system;

FIGS. 2A to 2C are diagrams showing an example of the configuration of the conventional optical wavelength-division multiplex(ing) access system;

25 FIG. 3 is a diagram showing an example of an additional installation in the conventional optical wavelength-division multiplex(ing) access system;

FIG. 4 is a diagram showing the characteristics of a WDM coupler and an optical modulator in the additionally installed configuration;

FIGS. 5A and 5B are diagrams showing a first
5 embodiment of a wavelength-division multiplex(ing) access system according to the present invention;

FIG. 6 is a diagram showing the characteristics of a WDM coupler and an optical modulator according to a first embodiment;

10 FIG. 7 is a diagram showing the characteristics of a WDM coupler and an optical modulator according to a second embodiment;

FIG. 8 is a diagram showing the characteristics of a WDM coupler and an optical modulator according to a
15 third embodiment;

FIG. 9 is a diagram showing another example of the configuration of a wavelength multi/demultiplexer 21a according to the first embodiment;

FIG. 10 is a diagram showing another example of the
20 configuration of the wavelength multi/demultiplexer 21a according to the first embodiment;

FIGS. 11A and 11B are diagrams showing a fourth embodiment of a wavelength-division multiplex(ing) access system according to the present invention;

25 FIGS. 12A and 12B are diagrams showing a fifth embodiment of a wavelength-division multiplex(ing) access system according to the present invention; and

FIGS. 13A to 13D are diagrams showing the characteristics of assignment of standard and additional wavelength bands according to the present invention.

5

BEST MODE FOR CARRYING OUR THE INVENTION

(First Embodiment)

FIGS. 5A and 5B show a first embodiment of a
10 wavelength-division multiplex(ing) access system
according to the present invention. In FIG. 5A, a
center apparatus (OLT) 10 and a wavelength
multi/demultiplex(ing) apparatus 10 are connected
together in a multiplex section via multiplex section
15 optical fibers 1 and 2. The wavelength
multi/demultiplex(ing) apparatus 20 and a plurality of
optical network units (ONUs) 30-1 to 30-n are
connected together in an access section via access
section optical fibers 3 and 4. In this case, the ONUs
20 30-1 to 30-n are standard, while the ONUs 30-n+1 to
30-n+m are additional.

According to the present invention, for the
standard ONUs 30-1 to 30-n+m, wavelengths λ_{d1} to λ_{dn} in
a wavelength band D_a are assigned to downlink signals.
25 Wavelengths λ_{u1} to λ_{un} in a wavelength band U_a are
assigned to uplink signals. Further, for the
additional ONUs 30-n+1 to 30-n+m, wavelengths λ_{dn+1} to

λ_{dn+m} in a wavelength band Db are assigned to downlink signals. Wavelengths λ_{un+1} to λ_{un+m} in a wavelength band Ub are assigned to uplink signals. Moreover, the present invention is characterized in that the

5 wavelength bands Ua and Ub are set adjacent to each other. In the example of the present embodiment, the wavelength bands Da, Ua, Ub, and Db are assigned on the wavelength axis in this order. The order may be reversed.

10 The OLT 10 comprises a standard transmission section (Sa) 11a that multiplexes the wavelengths of and transmits downlink optical signals in the wavelength band Da (λ_{d1} to λ_{dn}) and optical carriers for uplink signals in the wavelength band Ua (λ_{u1} to λ_{un}). The OLT 10 also comprises an additional transmission section (Sb) 11b that multiplexes the wavelengths of and transmits downlink optical signals in the wavelength band Db (λ_{dn+1} to λ_{dn+m}) and optical carriers for uplink signals in the wavelength band Ub (λ_{un+1} to λ_{un+m}). Moreover, the OLT 10 comprises a standard reception section (Ra) 12a that receives uplink optical signals in the wavelength band Ua (λ_{u1} to λ_{un}) and an additional reception section (Rb) 12b that receives uplink optical signals in the wavelength band Ub (λ_{un+1} to λ_{un+m}).
25

A WDM coupler 13d multiplexes the wavelengths of standard and additional downlink optical signals and

optical carriers for uplink signals transmitted by the standard transmission section 11a and the additional transmission section 11b. The WDM coupler 13d then transmits the resultant signals to the wavelength multi/demultiplex(ing) apparatus 20 via the multiple section optical fiber 1. The wavelength multi/demultiplex(ing) apparatus 20 uses a WDM coupler 22d to separate the standard wavelength bands Da and Ua from the additional wavelength bands Db and Ub. The wavelength multi/demultiplex(ing) apparatus 20 uses wavelength multi/demultiplexers 21a and 21b to divide the wavelength bands separated, into downlink optical signals and optical carriers for uplink signals of the respective wavelengths. Pairs of downlink optical signals of the wavelengths λ_{d1} to λ_{dn} and optical carriers for uplink signals of the wavelengths λ_{u1} to λ_{un} which have been divided by the wavelength multi/demultiplexer 21a are transmitted to the corresponding ONUs 30-1 to 30-n via the access section optical fiber 3. Pairs of downlink optical signals of the wavelengths λ_{dn+1} to λ_{dn+m} and optical carriers for uplink signals of the wavelengths λ_{un+1} to λ_{un+m} which have been divided by the AWG 61b are transmitted to the corresponding ONUs 30-n+1 to 30-n+m via the access section optical fiber 3.

WDM couplers 31 of the standard ONUs 30-1 to 30-n+m have a common transmission characteristic that they

separate the wavelength bands Da and Db for downlink signals from the wavelength bands Ua and Ub for uplink signals. Optical modulators 33 are equally characterized by modulating optical carriers of the adjacent wavelength bands Ua and Ub. Each of the ONUs uses an optical receiver (R) to receive a downlink optical signal of the wavelength within the wavelength bands Da and Db demultiplexed by the WDM coupler 31 which wavelength is assigned to the ONU. Each ONU uses an optical modulator (M) 33 to modulate an optical carrier for an uplink signal of the wavelength within the wavelength bands Ua and Ub which is assigned to the ONU to obtain an uplink optical signal and then transmits the signal. The uplink optical signal transmitted by each ONU is transmitted to the wavelength multi/demultiplexer 21a or 21b of the wavelength multi/demultiplex(ing) apparatus 20 via the access section optical fiber 4. A WDM coupler 22u demultiplexes the standard and additional uplink optical signals wavelength-multiplexed by the wavelength multi/demultiplexers 21a and 21b. The WDM coupler 22u then transmits the resultant signals to the OLT 10 via the uplink multiple section optical fiber 2. The OLT 10 uses a WDM coupler 13u to separate the standard wavelength band Ua from additional wavelength band Ub. The standard and additional reception sections 12a and 12b receive the wavelength

bands separated.

FIG. 6 shows the characteristics of the WDM coupler and optical modulator according to the first embodiment. As shown in FIG. 6A, according to the present embodiment, the wavelength bands Da, Ua, Ub, and Db are assigned on the wavelength axis in this order. The transmission characteristics of the WDM couplers 13d and 13u of the OLT 10 and of the WDM couplers 22d and 22u of the wavelength multi/demultiplex(ing) apparatus 20 may be such that they can merge or separate the standard wavelength bands Ua and Da with or from the additional wavelength bands Ub and Db as shown in FIG. 6B. Accordingly, all of these components may conform to the same specifications. In this case, the standard transmission sections 11a and 12a are connected to reflection ports of the WDM couplers 13d and 13u. The additional transmission sections 11b and 12b are connected to transmission ports of the WDM couplers 13d and 13u. The standard wavelength multi/demultiplexer 21a is connected to the reflection port of each of the WDM couplers 22d and 22u. The additional wavelength multi/demultiplexer 21b is connected to the transmission port of each of the WDM couplers 22d and 22u.

Moreover, the WDM couplers 31 of the standard ONUs 30-1 to 30-n and additional ONUs 30-n+1 to 30-n-m may

have a transmission characteristic that they separate the wavelength bands Da and Db for downlink optical signals from the wavelength bands Ua and Ub for optical carriers for uplink signals as shown in FIG.

5 6C. In other words, the wavelength bands Ua and Ub of optical carriers for uplink signals (uplink optical signals) are set adjacent to each other. Thus, the WDM couplers 31 may have a transmission characteristic that they demultiplex and send optical carriers for
10 uplink signals in the wavelength bands Ua and Ub to their transmission ports and downlink optical carriers in the wavelength bands Da and Db to their reflection ports. Thus, common devices can be used as the WDM couplers 31 of both standard and additional ONUs.
15 Likewise, for the optical modulators 33 of the standard and additional ONUs, the wavelength bands Ua and Ub for optical carriers for uplink signals are set adjacent to each other. Thus, the optical modulators 33 may be composed of modulators having a continuous
20 operating band as shown in FIG. 6D and conforming to the same specifications.

For example, if the wavelength bands Da, Ua, Ub, and Db are set at 1,525 to 1,545 nm, 1,545 to 1,565 nm, 1,570 to 1,590 nm, and 1,590 to 1,610 nm, respectively,
25 the optical modulators 33 of the standard and additional ONUs may have an operating band of about 45 nm between 1545 and 1590 nm. This allows the ONUs

including the WDM couplers 31 to be composed of one type of devices.

Further, the standard downlink optical signals and uplink optical signals (optical carriers for uplink signals) use a wavelength band of 1,525 to 1,565 nm. The additional downlink optical signals and uplink optical signals (optical carriers for uplink signals) use a wavelength band of 1,570 to 1,610 nm. Therefore, for example, an erbium-doped fiber amplifier or a gain-shifted erbium-doped fiber amplifier (gain-shifted EDFA) can be used in wavelength multi/demultiplex(ing) apparatus 20 to amplify the whole of each wavelength band at a time.

(Second Embodiment)

FIG. 7 shows the characteristics of a WDM coupler and an optical modulator according to a second embodiment. The configuration of the second embodiment of the wavelength-division multiplex(ing) access system according to the present invention is similar to that of the first embodiment, shown in FIG. 5A. In the example of the present embodiment, the wavelength bands Da, Ua, Ub, and Db are assigned on the wavelength axis in this order. The order may be reversed.

The transmission characteristics of the WDM couplers 13d and 13u of the OLT 10 and of the WDM couplers 22d and 22u of the wavelength

multi/demultiplex(ing) apparatus 20 may be such that they can merge or separate the standard wavelength bands U_a and D_a with or from the additional wavelength bands U_b and D_b as shown in FIG. 7B. Accordingly, the
5 WDM couplers 13d, 13u, 22D, and 22u may all conform to the same specifications. In this case, the standard transmission sections 11a and 12a are connected to reflection ports of the WDM couplers 13d and 13u. The additional transmission sections 11b and 12b are
10 connected to transmission ports of the WDM couplers 13d and 13u. The standard wavelength multi/demultiplexer 21a is connected to the reflection port of each of the WDM couplers 22d and 22u. The additional wavelength multi/demultiplexer 21b is
15 connected to the transmission port of each of the WDM couplers 22d and 22u.

Moreover, the WDM couplers 31 of the standard ONUs 30-1 to 30-n and additional ONUs 30-n+1 to 30-n-m may have a transmission characteristic that they separate
20 the wavelength bands D_a and D_b for downlink optical signals from the wavelength bands U_a and U_b for optical carriers for uplink signals as shown in FIG. 7C. In other words, the wavelength bands U_a and U_b of optical carriers for uplink signals (uplink optical
25 signals) are set adjacent to each other. Thus, the WDM couplers 31 may have a transmission characteristic that they demultiplex and send optical carriers for

uplink signals in the wavelength bands Ua and Ub to their transmission ports and downlink optical carriers in the wavelength bands Da and Db into their reflection ports. Thus, common devices can be used as
5 the WDM couplers 31 of both standard and additional ONUs. Likewise, for the optical modulators 33 of the standard and additional ONUs, the wavelength bands Ua and Ub for optical carriers for uplink signals are set adjacent to each other. Thus, the optical modulators
10 33 may be composed of modulators having a continuous operating band as shown in FIG. 7D and conforming to the same specifications.

For example, if the wavelength bands Da, Ua, Ub, and Db are set at 1,525 to 1,545 nm, 1,545 to 1,565 nm,
15 1,570 to 1,590 nm, and 1,590 to 1,610 nm, respectively, the optical modulators 33 of the standard and additional ONUs may have an operating band of about 40 nm between 1525 and 1565 nm. This allows the ONUs including the WDM couplers 31 to be composed of one
20 type of devices.

(Third Embodiment)

FIG. 8 shows the characteristics of a WDM coupler and an optical modulator according to a third embodiment. The configuration of the third embodiment
25 of the wavelength-division multiplex(ing) access system according to the present invention is similar to that of the first embodiment, shown in FIG. 5A. In

the example of the present embodiment, the wavelength bands Da, Ua, Ub, and Db are assigned on the wavelength axis in this order. The order may be reversed.

5 The transmission characteristics of the WDM couplers 13d and 13u of the OLT 10 and of the WDM couplers 22d and 22u of the wavelength multi/demultiplex(ing) apparatus 20 may be such that they can merge or separate the standard wavelength
10 bands Ua and Da with or from the additional wavelength bands Ub and Db as shown in FIG. 8B. Accordingly, the WDM couplers 13d, 13u, 22D, and 22u may all conform to the same specifications. In this case, the standard transmission sections 11a and 12a are connected to
15 reflection ports of the WDM couplers 13d and 13u. The additional transmission sections 11b and 12b are connected to transmission ports of the WDM couplers 13d and 13u. The standard wavelength multi/demultiplexer 21a is connected to the reflection
20 port of each of the WDM couplers 22d and 22u. The additional wavelength multi/demultiplexer 21b is connected to the transmission port of each of the WDM couplers 22d and 22u.

Moreover, the WDM couplers 31 of the standard ONUs
25 30-1 to 30-n and additional ONUs 30-n+1 to 30-n-m may have a transmission characteristic that they separate the wavelength bands Da and Db for downlink optical

signals from the wavelength bands Ua and Ub for optical carriers for uplink signals as shown in FIG. 8C. In other words, the wavelength bands Ua and Ub of optical carriers for uplink signals (uplink optical signals) are set adjacent to each other. Thus, the WDM couplers 31 may have a transmission characteristic that they demultiplex and send optical carriers for uplink signals in the wavelength bands Ua and Ub to their transmission ports and downlink optical carriers in the wavelength bands Da and Db to their reflection ports. Thus, common devices can be used as the WDM couplers 31 of both standard and additional ONUs. Likewise, for the optical modulators 33 of the standard and additional ONUs, the wavelength bands Ua and Ub for optical carriers for uplink signals are set adjacent to each other. Thus, the optical modulators 33 may be composed of modulators having a continuous operating band as shown in FIG. 8D and conforming to the same specifications.

For example, if the wavelength bands Da, Ua, Ub, and Db are set at 1,525 to 1,545 nm, 1,545 to 1,565 nm, 1,570 to 1,590 nm, and 1,590 to 1,610 nm, respectively, the optical modulators 33 of the standard and additional ONUs may have an operating band of about 40 nm between 1525 and 1565 nm. This allows the ONUs including the WDM couplers 31 to be composed of one type of devices.

(Example of Configuration of Wavelength
Multi/Demultiplexer 21a, 21b)

The wavelength multi/demultiplexer 21a of the
wavelength multi/demultiplex(ing) apparatus 20, shown
5 in FIGS. 5A and 5B are assumed to be an AWG that
demultiplexes a pair of a downlink optical signal of
the wavelength λ_{d1} to λ_{dm} and an optical carrier for an
uplink signal of the wavelength λ_{u1} to λ_{un} into the
same port. The spacing between the paired signals is
10 set equal to the FSR (or its integral multiple) as
shown in FIG. 6A. However, the multiplexing of uplink
optical signals of the wavelengths λ_{u1} to λ_{un} does not
necessarily require the functions of the AWG. It is
possible to use a configuration in which the AWG 23 is
15 used to separate downlink optical signals from optical
carriers for uplink signals and in which a multiplexer
24 is used to multiplex optical carriers for uplink
signals as shown in FIG. 9.

As shown in FIG. 10, a demultiplexer 25-1 that
20 demultiplexes downlink optical signals of the
wavelengths λ_{d1} to λ_{dn} and a demultiplexer 25-2 that
demultiplexes optical carriers for uplink signals of
the wavelengths λ_{u1} to λ_{un} may be used instead of the
AWG 23 in FIG. 9. A WDM coupler 26 may then separates
25 downlink optical signals in the wavelength band D_a
from optical carriers for uplink signals in the
wavelength band U_a . The WDM coupler 26 may then input

the signals to the demultiplexers 25-1 and 25-2. WDM couplers 26-1 to 26-n may then multiplex the pairs of the downlink optical signals and optical carriers for uplink signals. This configuration does not require
5 the FSR of the AWG to be set for the wavelength spacing between the paired downlink optical signal and uplink optical carrier corresponding to each ONU. The wavelength spacing may be set at an arbitrary value.

The configuration of the wavelength
10 multi/demultiplexer 21b is similar to that of the wavelength multi/demultiplexer 21a, shown above. In a configuration in which an AWG is used as the wavelength multi/demultiplexer, the second embodiment has a larger wavelength spacing between the downlink
15 optical signal and uplink optical carrier corresponding to each ONU as shown in FIG. 7A. Further, in a configuration in which an AWG is used as the wavelength multi/demultiplexer, the third embodiment has a larger wavelength spacing between the downlink
20 optical signal and uplink optical carrier corresponding to each additional ONU as shown in FIG. 8A. Thus, the wavelength multi/demultiplexers 21a and 21b must be composed of AWGs according to each of the second and third embodiments.

25 (Fourth and Fifth Embodiments)

According to the first embodiment, optical carriers for uplink signals supplied by the OLT 10 to

each ONU are transmitted while multiplexing the wavelengths of the carriers. The wavelength multi/demultiplex(ing) apparatus 20 then demultiplexes the optical carriers for uplink signals of the
5 respective wavelengths and supplies the resultant signals to the corresponding ONUs. Each of the ONUs modulates the optical carrier for the uplink signal to obtain an uplink optical signal and then transmits the signal. A fourth and fifth embodiments shown below
10 have optical transmitters that transmit uplink optical signals to the respective ONUs. However, the fourth and fifth embodiments assign the wavelengths as shown in the first to third embodiments. The fourth and fifth embodiments thus allow the optical transmitters
15 to operate in a common operating band. These embodiments also allow common devices to be used as both standard and additional ONUs.

FIGS. 11A and 11B show a fourth embodiment of a wavelength-division multiplex(ing) access system
20 according to the present invention. The OLT 10 according to the present embodiment comprises a standard transmission section (Sa) 14a that multiplexes the wavelengths of and transmits downlink optical signals in the wavelength band Da (λ_{d1} to λ_{dn})
25 and an additional transmission section (Sb) 14b that multiplexes the wavelengths and transmits downlink optical signals in the wavelength band Db (λ_{dn+1} to

λ_{dn+m}). Further, the OLT 10 comprises a standard reception section (Ra) 12a that receives uplink optical signals in the wavelength band Ua (λ_{u1} to λ_{un}) and an additional reception section (Rb) 12b that
5 receives uplink optical signals in the wavelength band Ub (λ_{un+1} to λ_{un+m}).

The WDM coupler 13d multiplexes of the wavelengths of standard and additional downlink optical signals transmitted by the standard and additional
10 transmission sections 14a and 14b. The WDM coupler 13d then transmits the resultant signals to the wavelength multi/demultiplex(ing) apparatus 20 via the multiple section optical fiber 1. The wavelength multi/demultiplex(ing) apparatus 20 uses the WDM
15 coupler 22d to separate the standard wavelength band Da from the additional wavelength band Db. The wavelength multi/demultiplex(ing) apparatus 20 uses the wavelength multi/demultiplexers 21a and 21b to demultiplex downlink optical signals of the respective
20 wavelengths. The downlink optical signals of the wavelengths λ_{d1} to λ_{dn} demultiplexed by the wavelength multi/demultiplexer 21a are transmitted to the corresponding ONUs 30-1 to 30-n via the access section optical fiber 3. The downlink optical signals of the
25 wavelengths λ_{dn+1} to λ_{dn+m} demultiplexed by the wavelength multi/demultiplexer 21b are transmitted to the corresponding ONUs 30-n+1 to 30-n+m via the access

section optical fiber 3.

Each of the ONUs 30-1 to 30-n+m uses an optical receiver (R) 32 to receive a downlink optical signal of the wavelength within the wavelength bands Da and Db which is assigned to the ONU. Each of the ONUs 30-1 to 30-n+m uses an optical transmitter (S) 35 to transmit an uplink optical signal of the wavelength within the wavelength bands Ua and Ub which is assigned to the ONU. Uplink optical signals transmitted by the ONUs are transmitted to the wavelength multi/demultiplexer 21a and 21b of the wavelength multi/demultiplex(ing) apparatus 20 via the access section optical fiber 4. Then, the WDM coupler 22u multiplexes the standard and additional uplink optical signals wavelength-multiplexed by the wavelength multi/demultiplexer 21a and 21b. The WDM coupler 22u transmits the resultant signals to the OLT 10 via the multiplex section optical fiber 2. The OLT 10 uses the WDM coupler 13u to separate the uplink optical signals into the standard wavelength band Ua and the additional wavelength band Ub. The standard and additional reception sections 12a and 12b receive the wavelength bands Ua and Ub, respectively.

In the present embodiment, the WDM coupler 13d of the OLT 10 and the WDM coupler 22d of the wavelength multi/demultiplex(ing) apparatus 20 merge and separate the standard wavelength band Da with and from the

additional wavelength band Dn. The WDM coupler 13u of the OLT 10 and the WDM coupler 22u of the wavelength multi/demultiplex(ing) apparatus 20 merge and separate the standard wavelength band Ua with and from the additional wavelength band Ub. Thus, the WDM couplers 13d and 13u, 22d, and 22u may all have a transmission characteristic shown in FIG. 6B, 7B, or 8B. The wavelength multi/demultiplexer 21a of the wavelength multi/demultiplex(ing) apparatus 20 uses a single element (AWG) to provide a function for demultiplexing downlink optical signals in the standard wavelength band Da and multiplexing uplink optical signals in the standard wavelength band Ua. However, the multiplexing and demultiplexing may be individually carried out by a multiplexer and a demultiplexer. This also applies to the wavelength multi/demultiplexer 21b.

Moreover, the optical transmitter 35 of each ONU according to the present embodiment sets the standard and additional wavelengths Ua and Ub adjacent to each other. Accordingly, the optical transmitters 35 may have the continuous operating band shown in FIG. 6D, 7D, or 8D and conform to the same specifications. For example, if the wavelength bands Da, Ua, Ub, and Db are set at 1,525 to 1,545 nm, 1,545 to 1,565 nm, 1,570 to 1,590 nm, and 1,590 to 1,610 nm, respectively, the ONUs can transmit optical carriers for uplink signals of the respective set wavelengths by using, as the

optical transmitters 35, wavelength variable light sources operating in an operating band of 1,545 to 1,590 nm. Alternatively, the optical transmitters 35 may modulate and transmit broadband light containing the wavelength bands Ua and Ub. Then, the wavelength multi/demultiplexers 21a and 21b spectrum-slices the light transmitted.

FIGS. 12A and 12B show a fifth embodiment of a wavelength-division multiplex(ing) access system according to the present invention. The present embodiment is characterized in that the OLT 1 and the wavelength multi/demultiplex(ing) apparatus 20 are connected together in the multiplex section via the single multiplex section optical fiber 1 and in that the wavelength multi/demultiplex(ing) apparatus 20 and each ONU are connected together in the access section via the single access section optical fiber 3.

In the present embodiment, the WDM coupler 13 of the OLT 10 and the WDM coupler 22 of the wavelength multi/demultiplex(ing) apparatus 20 merge and separate the standard wavelength bands Da and Ua with and from the additional wavelength bands Db and Ub. Thus, the WDM couplers 13 and 22 may have the transmission characteristic shown in FIG. 6B, 7B, or 8C. Each ONU also comprises a WDM coupler 31 that separates the wavelength band Da, Db for downlink optical signals from the wavelength band Ua, Ub for uplink optical

signals. The WDM coupler may have the transmission characteristic shown in FIG. 6C, 7C, or 8C. The OLT 10 also comprises a WDM coupler 15a that separates the wavelength band Da for standard downlink optical signals from the wavelength band Ua for standard uplink optical signals which bands are merged or separated by the WDM coupler 13. Moreover, the OLT 10 further comprises a WDM coupler 15b that separates the wavelength band Db for additional downlink optical signals from the wavelength band Ub for additional uplink optical signals. These WDM couplers may have the transmission characteristic shown in FIG. 6C, 7C, or 8C. In the OLT 10, the functions of the WDM coupler 13 may be replaced with the functions of the WDM couplers 15a and 15b.

(Other Embodiments)

In the description of the above embodiments, it is assumed that m ONUs are added to n standard ONUs. However, the above embodiments also apply to the case in which $n+m$ ONUs are divided into a group of n ONUs and a group of m ONUs so that one of the groups is used for the standard, while the other is used for the addition. That is, a characteristic of the present invention is a manner of arranging standard and additional wavelength bands if each of the wavelength band U for uplink optical signals and the wavelength band D for downlink optical signals is divided into

two.

FIGS. 13A to 13D show the characteristic relating to the assignment of standard and additional wavelengths according to the present invention. In
5 FIGS. 13A to 13D, "a" denotes the standard, and "b" denotes the addition. In this case, with the method shown in FIG. 13A, each of the wavelength bands U and D is divided on the wavelength axis. The resultant wavelength bands Ua, Ub, Da, and Db are arranged in
10 this order (or the reverse order). In contrast, with the method shown in FIGS. 13B, 13C, and 13D, the wavelength bands Ua and Ub are adjacent to each other, and at least either the wavelength bands Ua and Da or the wavelength bands Ub and Db are adjacent to each
15 other (as shown by underlines in the figures). This method allows all the ONUs to conform to the same specifications as shown in the above embodiments. FIG. 13A corresponds to FIG. 4 (conventional example), and FIGS. 13B, 13C, and 13D correspond to FIG. 6 (first
20 embodiment), FIG. 7 (second embodiment), and FIG. 8 (third embodiment).

INDUSTRIAL APPLICABILITY

25 As described above, according to the present invention, the wavelength band Ua for uplink optical signals assigned to the standard ONUs and the

wavelength band U_b for uplink optical signals assigned to the additional ONUs are set adjacent to each other. This makes it possible to minimize the operating band or light emission band of uplink optical signal

5 transmitting means (optical modulators, optical transmitters composed of wavelength variable light sources, or optical transmitters composed of broadband light sources) for using the standard and additional ONUs to transmit uplink optical signals. As a result,

10 all the ONUs may conform to the same specifications.

Further, in a configuration in which the OLT supplies optical carriers for uplink signals to the ONUs, the wavelength band demultiplexers of the ONUs, which separates optical carriers for uplink signals

15 from downlink optical signals, may all conform to the same specifications. Thus, ONUs, accommodated in the OLT, can be additionally installed.